

Wuxi Tefa Decoration Material Co., Ltd.

NO.5 HUAQING INTELLIGENT PARK,HUIZHAN DISTRICT,WUXI,JIANGSU,CHINA
Tel/Wechat/Whatsapp:+86 18751567592 E-mail: mara@topvcfloor.com

Technical Data for direction homogeneous floor

Total Thickness	EN ISO 24346	2.0/2.5/3.0mm
Size:Lenght/Width	EN ISO 24341	2.0m*20m
Total Weight	EN ISO 23997	2.0mm:3100g/m ²

CLASSIFICATION

Fire Rating	GB8624-2012	Class	B-S1
Toxic Testing	GB18586-2001	-	Good
Electrical Resistance	EN1081	Ω	$>3.0*10^{10}$
Slip Resistance Dry	EN13893	-	≥ 0.3
Slip Resistance Wet	DIN51130	Class	R9

PRODUCT PERFORMANCE

Dimensional stability	EN434-1994	%	≤ 0.4
Thermal Conductivity	EN12667	W/(m.k)	0.050
Castor Wheel Test	EN425	-	SUITABLE
Wear Resistance	EN660.2	mm ³	≤ 3.5
Abrasion Group	EN649	group	p
Residual Indentation	EN ISO 24343.1	mm	约0.04
colour Fastness	EN ISO 105-B02	degree	6
Chemical Product Resistance	EN ISO 26987	-	GOOD
Antibacterial Property	EN ISO 846-C	-	无细菌滋生 No bacteria
Toxic Testing	GB18586-2001	-	Qualified
Hygiene Treatment	MRSA	-	VERY GOOD
Impact Sound Reduction	EN ISO 10140/1 EN ISO 717/2	-	APPROX.+4DB
Surface Treatment	-	-	PUR

APPLICATIONS

It is widely used in public places, administrative and commercial buildings, easy to clean and maintain, and busy areas with long service life. For example: hospitals, schools, laboratories, offices and other places.